

Product Specifications

WELE - LB Series LB-x33

Specification/ Machine model	Unit	LB-433	LB-533	LB-633	LB-733	LB-833	LB-1033	
X axis travel	mm (in)	4060 (159.8)	5060 (199.2)	6060 (238.6)	7060 (277.9)	8060 (317.3)	10060 (396)	
Y axis travel	mm (in)	3350 (131.8)						
Z axis travel	mm (in)	800 (31.5)						
Table dimension (X direction)	mm (in)	4000 (157.5)	5000 (196.9)	6000 (236.2)	7000 (275.6)	8000 (314.9)	10000 (393.7)	
Table dimension (Y direction)	mm (in)	2400 (94.4)				2500 (98.4)		
Table loading	kg (lb)	15000 (33069)	18000 (39683)	20000 (44092)	22000 (48501)	25000 (55115)	25000 (55115)	
Spindle motor power	kW (HP)	22/26 (30/35)						
Spindle speed	rpm	10-6000						
Spindle taper		BT#50 (ISO 50)						
Rapid feedrate - X axis	mm(in)/min	18000 (708.7)	12500 (492.1)	9000 (354.3)	6000 (236.2)	5000 (196.8)	4000 (157.4)	
Rapid feedrate - Y axis	mm(in)/min	20000 (787.4)						
Rapid feedrate - Z axis	mm(in)/min	15000 (590.6)						
Cutting feedrate	mm(in)/min	1-10000 (0.04-393.7)		1-9000 (0.04-354.3)	1-6000 (0.04-236.2)	1-5000 (0.04-196.8)	1-4000 (0.04-157.4)	
Capacity of tool magazine	pcs	32						
Max. diameter of tool / Adjacent pocket empty	mm (in)	127/215 (5.0/8.5)						
Max. length of tool	mm (in)	400 (15.7)						
Max. weight of tool	kg (lb)	20 (44)						
Positioning accuracy (JIS 6338)	mm (in)	±0.015 (±0.006)						
Positioning accuracy (VDI/DGQ 3441)	mm (in)	P _s ≤0.025(0.000984)	P _s ≤0.025(0.000984)	P _s ≤0.030(0.001181)	P _s ≤0.035(0.001378)	P _s ≤0.035(0.001378)	P _s ≤0.045(0.001772)	
Repeatability accuracy (JIS 6338)	mm (in)	±0.003 (±0.0001)						
Repeatability accuracy (VDI/DGQ 3441)	mm (in)	P _s ≤0.020(0.000787)	P _s ≤0.020(0.000787)	P _s ≤0.025 (0.000984)	P _s ≤0.028(0.001102)	P _s ≤0.028(0.001102)	P _s ≤0.032(0.00126)	
Length of the machine	mm (in)	10590 (416.9)	12660 (498.4)	14750 (580.7)	17250 (679.1)	20000 (787.4)	23070 (908.2)	
Width of the machine	mm (in)	6500 (255.9)						
Height of the machine	mm (in)	5250 (206.6)						
Weight of the machine	kg (lb)	---	---	---	---	---	---	